

PVC/VINYL ADHESIVE TAPE

TECHNICAL DATA SHEET

TYPICAL APPLICATIONS & ADVANTAGES

- High tensile strength and stability, high immediate tack and adhesion on various surfaces.
- Smooth & low noise unwinding
- Product suitable for recycling purposes.
- Once applied, ideal for storage in extreme temperature conditions and high moisture environments.
If being applied in cooler temperatures, the product must be applied before storing.



CONSTRUCTION

- Backing: Unplastified clear PVC film
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Available in white or clear.

TECHNICAL DATA

	METRIC
Backing Thickness	32/33 Micron
Total Thickness	50/51 Micron
Peel Adhesion	2,4 N/cm
Tensile Strength	47 N/cm
Elongation at Break	60%
Service Temperature	-25°C / +65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months.
Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.