

POLYPROPYLENE SELF-ADHESIVE TAPE

BOPP Tape

TECHNICAL DATA SHEET

TYPICAL APPLICATIONS & ADVANTAGES

- ✔ Suitable either with a manual dispenser or automated application.
- ✔ Easy unwinding.
- ✔ Good initial tack with a hotmelt adhesive with easy application.
- ✔ The adhesive high cohesion value guarantees a long lasting adhesion and a safe storage even with temperature variation and good for use in extreme cold temperatures.

CONSTRUCTION

- ✔ Backing: Biaxially oriented polypropylene clear film.
- ✔ Adhesive: Hotmelt
- ✔ Colour: Available in white or clear.

TECHNICAL DATA

	<i>METRIC</i>
Total Thickness	44 Micron
Peel Adhesion	12,5 N/inch
Tensile Strength	155 N/mm ²
Elongation at break	150%
Service Temperature	-10°C / +60°C
Application Temperature	6°C / +45°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months.
Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.

